


### Screw Pin Bow Shackles with screw collar pin

- **Material** : bow: high tenstile, pin: alloy
- **Standard** : generally to US Fed. Spec. RR-C-271
- **Finish** : hot dipped galvanised
- **Certificates** : as standard a certificate of conformity is supplied
- **FOS** : 6 : 1


working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	width bow	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm	kg
0.33	5	6	14	9.5	22	15	0.03
0.5	6	8	16	12	29	20	0.05
0.75	8	10	19	13.5	31	21	0.09
1	10	11	23	17	37	26	0.14
1.5	11	13	27	19	43	29	0.17
2	13	16	30	20	48	33	0.33
3.25	16	19	38	27	60	43	0.62
4.75	19	22	46	32	71	50	1.07
6.5	22	25	53	36	84	58	1.64
8.5	25	28	61	43	95	68	2.28
9.5	28	32	68	46	108	74	3.36
12	32	35	76	51	119	82	4.31
13.5	35	38	84	57	133	92	6.14
17	38	42	92	60	146	98	7.81
25	45	50	106	73	177	127	12.61
35	50	57	119	83	197	138	18.33
55	65	70	145	105	260	185	37.90



### Safety Pin Bow Shackles with safety bolt

- **Material** : bow: high tenstile, pin: alloy
- **Standard** : generally to US Fed. Spec. RR-C-271
- **Finish** : hot dipped galvanised
- **Certificates** : as standard a certificate of conformity is supplied
- **FOS** : 6 : 1


working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	width bow	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm	kg
0.75	8	10	19	13.5	31	21	0.10
1	10	11	23	17	37	26	0.16
1.5	11	13	27	19	43	29	0.22
2	13	16	30	20	48	33	0.36
3.25	16	19	38	27	60	43	0.76
4.75	19	22	46	32	71	50	1.23
6.5	22	25	53	36	84	58	1.79
8.5	25	28	61	43	95	68	2.57
9.5	28	32	68	46	108	74	3.75
12	32	35	76	51	119	82	5.32
13.5	35	38	84	57	133	92	7.19
17	38	42	92	60	146	98	9.44
25	45	50	106	73	177	127	15.40
35	50	57	119	83	197	138	20.06
55	65	70	145	105	260	185	41.40



### Screw Pin Dee Shackles with screw collar pin

- **Material** : bow: high tensile, pin: alloy
- **Standard** : generally to US Fed. Spec. RR-C-271
- **Finish** : hot dipped galvanised
- **Certificates** : as standard a certificate of conformity is supplied
- **FOS** : 6 : 1


working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	weight each
tons	a mm	b mm	c mm	d mm	e mm	kg
0.5	6	8	16	12	22	0.05
0.75	8	10	19	13.5	26	0.08
1	10	11	23	17	32	0.13
1.5	11	13	27	19	37	0.20
2	13	16	30	20	41	0.27
3.25	16	19	38	27	51	0.57
4.75	19	22	46	32	60	1.19
6.5	22	25	53	36	71	1.43
8.5	25	28	61	43	81	2.16
9.5	28	32	68	46	90	3.06
12	32	35	76	51	100	4.11
13.5	35	38	84	57	111	5.28
17	38	42	92	60	122	7.24
25	45	50	106	73	146	12.14
35	50	57	119	83	171	16.86
55	65	70	145	105	203	32.65



### Safety Pin Dee Shackles with safety bolt

- **Material** : bow: high tensile, pin: alloy
- **Standard** : generally to US Fed. Spec. RR-C-271
- **Finish** : hot dipped galvanised
- **Certificates** : as standard a certificate of conformity is supplied
- **FOS** : 6 : 1


working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	weight each
tons	a mm	b mm	c mm	d mm	e mm	kg
2	13	16	30	20	41	0.34
3.25	16	19	38	27	51	0.67
4.75	19	22	46	32	60	1.14
6.5	22	25	53	36	71	1.75
8.5	25	28	61	43	81	2.52
9.5	28	32	68	46	90	3.45
12	32	35	76	51	100	4.91
13.5	35	38	84	57	111	6.24
17	38	42	92	60	122	8.40
25	45	50	106	73	146	14.26
35	50	57	119	83	171	18.53
55	65	70	145	105	203	35.33



## Commercial Bow Shackles with screw pin

- Material : bow: high tensile, pin: alloy
- Finish : electro-galvanised
- Note : not to be used for lifting applications

diameter bow	diameter pin	diameter eye	width inside	length inside	width bow	weight per 100 pcs
a mm	b mm	c mm	d mm	e mm	f mm	kg
8	8	16	16	32	24	6.0
10	10	20	20	40	30	11.6
11	11	22	22	44	33	15.5
12	12	24	24	48	36	20.1
14	14	28	28	56	42	31.9
16	16	32	32	64	48	47.6
20	20	40	40	80	60	93.1
22	22	44	44	88	66	124.0
25	25	50	50	100	75	182.0



## Commercial Dee Shackles with screw collar pin

- Material : mild steel, untreated, Grade 3
- Finish : electro-galvanised
- Note : not to be used for lifting applications

diameter bow	diameter pin	diameter eye	width inside	length inside	weight per 100 pcs
a mm	b mm	c mm	d mm	e mm	kg
5	5	10	10	19	1.47
6	6	12	12	25	2.56
8	8	16	16	32	6.06
10	10	20	20	38	11.80
11	11	22	22	44	15.80
12	12	24	24	51	20.50
14	14	28	28	53	32.50
16	16	32	32	64	48.50
20	20	40	40	76	94.70
22	22	44	44	89	126.00
25	25	50	50	100	185.00
28	28	56	56	115	260.00
32	32	64	64	127	388.00
38	38	76	76	152	650.00